



Cleaning Information for American Legends Series Doors

Our American Legends Series Doors are offered in white and a light color palette. If you have any questions or concerns regarding maintaining your door, please contact your installer or our factory. Failure to do so could cause the door to fail and/or void the warranty.

Cleaning your door

To ensure years of trouble-free performance, the face and edges of your vinyl sections are UV-resistant. For general cleaning of sections:

Use warm water and a dishwashing liquid soap, such as Dawn or Joy.

DO NOT use solutions containing acid or solvents like MEK, acetone, or Toluene.

DO NOT use Simple Green, as it may yellow the face of your door.

DO NOT use a power washer to remove dirt or stains from the door.

For more stubborn situations, Soft Scrub, Clorox Cleanup, or Clorox Outdoors can be used. You can also use 120-150 grit sandpaper on the solid vinyl overlays, but be sure to sand lightly and with the existing grain of the material. DO NOT use sandpaper on the vinyl clad steel (face of the door).

The door surface can be wiped with isopropyl denatured alcohol to remove any soap, cleaner residue, or dust.

DO NOT use heat or induce heat when field cleaning. Heat guns, heat lamps, and heaters could cause damage and may void your warranty.

Field Finishing your door

We do not recommend field finishing in any color other than white. Field finishing with any color other than white is done at the customer's risk and will void the warranty.